

Long Life Battery Robust GPS Asset Tracker for Outdoor Uses

WarriorX 100 4G

Robust and waterproof standalone asset tracker with up to 4.5 years battery life



| 160g (5.65oz)

| 82.8mm*66.9mm*35.7mm
(3.26" *2.63" *1.40")

| -30~80°C
(-22°F ~176°F)

| Replaceable 4000/8000mAh Battery
(optional)

Certificates:



*Please reach out to us if you need any certificates in particular

- 4G CAT 1 + 2G
- Compact Size
- IP67 Waterproof
- Robust Structure for Outdoor
- Super Long Life Battery
- Stolen Recovery Mode
- Low Battery Alarm
- MQTT Support
- Temper Alert
- Replaceable Non-rechargeable Battery
- GPS -> WIFI Scan -> LBS


Standby Time

(One Report per Day):

GPS off 4.5 years
 GPS on 3.5 years

**Assumes the device operates on LTE Cat1, with CSQ greater than 15, ambient temperature of 25°C and without working with any sensors.*

Container Tracking



Equipment Tracking



Trailer Tracking



PRODUCT SPECIFICATIONS

Network Specifications	
Operating Band	TLTE FDD Cat 1: B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B18/B19/ B20/B25/B26/B28/B66 LTE TDD Cat 1: B34/B38/B39/B40/B41 GSM:850/900/1800/1900 MHz
Data Transmission	LTE-FDD:Max.10Mbps (DL), Max.5Mbps (UL) LTE-TDD:Max.8.96Mbps(DL), Max.3.1Mbps (UL) GPRS: Max. 85.6Kbps (DL), Max. 85.6Kbps (UL)
GNSS Specifications	
GNSS Chipset	All-In-One GNSS Receiver
GNSS System	GPS + Glonass + Beidou + Galileo +QZSS
Receiver Type	47 tracking / 47 acquisitions- channel GNSS receiver
Sensitivity	Cold Start: < 15s (30s) Warm Start: < 2s (25s) Hot Start: < 2s (2s)
Horizontal Position Accuracy	Autonomous: < 1.5 m CEP
TTF@ -130 dBm with (without) EPO	Cold start: < 29s Warm start: < 27s Hot start: < 1s
Interfaces	
Data Transmission	4 Pin port TypeC USB
Network, GNSS, WiFi Antenna	Internal only
Indicator LED	Network, GNSS
FOTA	Yes
Temperature Sensor	1 temperature sensor
General Specifications	
Waterproof	IP67
Dimensions	82.8mm*66.9mm*35.7mm (3.26" *2.63" *1.40")
Weight	160g (5.65oz)
Battery	Non-rechargeable 4000 mAh/3.0V battery (8000mAh Battery Optional)
Standby Time	0.5 Year @ every 2 hrs reporting 2.5 Years @ every 12 hrs reporting 3.5 Years @ every 24 hrs reporting <small>*Assumes the device operates on LTE Cat1, with CSQ greater than 15, ambient temperature of 25°C and without working with any sensors.</small>
Data Communication	TypeC USB cable
Operating Temperature	-30°C ~ 80°C(-22°F ~ 176°C)
Air Interface Protocol	
Transmit Protocol	TCP, UDP, MQTT, SMS
Data Security & Encryption Option	MD5/ AES128
Scheduled Timing Report	Report position and status at preset intervals
Geo-fence	Support up to 64 internal geo-fence regions
Industry Certificates (planned)	
FCC, CE, RCM, CITC, TDRA, NBTC, Anatel	