

# SolarGuardX 120

Solar-powered BLE padlock for high value asset



- 535g (18.9 oz)
- 113.8mm\*90mm\*36.9mm (4.48" x 3.54" x 1.45") (Without rope)

- -40°C ~ 85°C (-40°F ~ 185°F)
- - Rechargeable Li-Polymer 2500mAh/ 3.7V

- Solar Panel Œ
- 6 Unlock by RFID, BLE, Master Lock
- 3 **Built-in Strong Magnet**
- ( Waterproof IP67
- **(** Firmware Over the BLE APP
- 3 **Motion Detection**
- Alarms for Locking, unlocking, (1) rope cutting and cover removal
- 0 Indicator Lights and Buzzer
- \*BLE 5.3 Long Range
- 2) **RFID**

### Certificates (planned):















\*Please reach out to us if you need any certificates in particular

#### **Fuel Tanker Monitoring**



#### **Container Monitoring**



#### Fleet Management



## SolarGuardx 120

Interfaces	
Charging Port	2 Pin 5V/DC
E-Lock Configuring Port	Type-C Connector
Indicator LED	Solar Charging Status, Battery, BLE, RFID
Power on Button	1
Temperature Sensor	1 Temperature Sensor
BLE 5.3 Long Range	Yes
General Specifications	
Waterproof	Waterproof
Dimensions	113.8mm*90mm*36.9mm (4.48" × 3.54" × 1.45")
Weight	535g (18.9 oz)
Battery	Rechargeable Li-Polymer 2500mAh/3.7V
Standby Time	Solar charging: Unlimited days
Charging	2 PIN (Recommend using 5V 3A adaptor, 3 hours charging)
Operating Temperature	-40°C~85°C (-40°F~185°F)
Transmission Range	Up to 1000m (3280 fts) (Open field, Power: 8 dBm (default), BLE 5.3 Long Range)
Mounting	Built-in Magnet
Alarms	Locking, Unlocking, Rope Cutting, Cover Removal
Industry Certifications (Planning)	
CE, RCM, IC, FCC, ATEX	





